






**INDUTTORI DI CALORE
HEATING INDUCTORS**

 MADE IN ITALY DATI TECNICI TECHNICAL FEATURES				
	Hi 3.7	Hi 5.5	Hi 13	Hi 18
Modello / Model	Cod. 05.066.11	Cod. 05.066.13	Cod. 05.066.27	Cod. 05.066.28
Max potenza / Max. power	3.7 Kw 16A	5 Kw 16A	13 Kw 32A	18 Kw 32A
Alimentazione / Power supply	230V single phase	400V 3ph	400V 3ph	400V 3ph
Frequenza regolabile (kHz) Frequency range (kHz)	15 ÷ 30 kHz	15 ÷ 30 kHz	15 ÷ 30 kHz	15 ÷ 30 kHz
Duty cycle	15'	30'	45'	60'
Cavo induttore Inductor cable length	4 mt	4 mt	4 mt	4 mt
Cavo alimentazione Power supply cable length	9 mt	9 mt	9 mt	9 mt
Capacità serbatoio Tank capacity	20 lt	20 lt	20 lt	20 lt
Raffreddamento a liquido Cooling system	✓	✓	✓	✓
Tastiera / Keyboard	✓	✓	✓	✓
Connessione elettrica Electrical connection	IEC 60309	IEC 60309	IEC 60309	IEC 60309
Dimensioni / Dimensions, cm	80 x 80 x 115	80 x 80 x 118	80 x 83 x 135	80 x 83 x 135
Peso / Weight, kg)	50 kg	67 kg	120 kg	130 kg
APPLICAZIONE / APPLICATION				
Carrozzerie / Car Body Shops	x	—	—	—
Gommisti / Tyre Shops	xxx	—	—	—
Meccanica auto / Car Mechanics	xxx	xx	—	—
Agri	xx	xxx	xxx	x
Autocarri/movimento terra Trucks/earth moving vehicles	—	x	xxx	xxx
Manutenzione/Industria/Nautica Trucks/earth moving vehicles	—	—	xxx	xxx