



Oil Exchanger for Automatic Transmissions

- A: 5" color touch display
- A: Gearbox outlet oil pressure measurement
- A: ATF's outlet oil pressure measurement
- B: Multilingual software
- C: AWS function: Automatic new oil Weight Set
- D: Automatic warm-up function (start of the automatic cycle when the optimal minimum temperature is reached)

- · Integrated oil flow inversion system
- E: Washing of the new oil suction circuit
- F: Dipstick kit
- **G**: Automatic additive injection
- H: Possibility to operate in automatic or manual mode
- I: Software and database updatable via USB
- J: Flowmeters with backlight (old/new)
- K: New and waste oil tanks
- L: 2 new sintered reusable filters with magnet
- \bullet M: Kit of couplings and hoses for European and Asiatic vehicles included
- N: Printer
- 0: SmartPack (12 months of free access to the online Database)
- P: Software for power steering oil change
- **Q**: Integrated database with brand, version, number of ratios, gearbox type, oil quantity, oil code
- WiFi module for data transmission / reception kit 01.000.328 on request*

SPIN CONNECT 4.0

Built-in WiFi module + SD Card Cod. 01.000.328*



*to be ordered at the same time as the ATF station

ATF S-Drive 5000 SW Cod. 02.023.53




MADE IN ITALY



S-DRIVE 5000 SW









5



