

NITROPOINT
LINE

NITROGEN GENERATORS WITH PERMEABLE MEMBRANE SYSTEM FOR INFLATING TYRES OF CARS, VANS AND BUSES

- Minimum purity: 95%
- Built-in, oil separating and active carbon filters
- Automatic condensation overflow
- A: Air-nitrogen switch
- B: Extra outlet for external tank
- C: Nitrogen outlet pressure gauge
- D: Filter blockage check instrument
- E: Inflating/deflating Michelin gun with Venturi meter and 8 mt spiral hose
- F: 20 caps for tyres inflated with nitrogen

OPTIONAL ACCESSORIES

Cod. 03.000.14

Kit of caps for tyres inflated with nitrogen, 100 pcs

Cod. 03.006.01

Kit of spare cartridges for Nitropoint 10 / Nitropoint 20, 3 pcs

Cod. 03.006.02

Kit of spare cartridges for Nitropoint 1 / Nitropoint 3, 2 pcs

Important: please specify the serial number in the order



STANDARD ACCESSORIES



NITROPOINT <i>Line</i>	NITROPOINT 1 Cod. 03.002.02	NITROPOINT 3 Cod. 03.002.04	NITROPOINT 10 Cod. 03.002.06	NITROPOINT 20 Cod. 03.002.22
Flow capacity	1,2 Nm ³ /h 10 bar (145 PSI)	3,6 Nm ³ /h 10 bar (145 PSI)	12 Nm ³ /h 10 bar (181 PSI)	24 Nm ³ /h 10 bar (181 PSI)
Purity	Min. 95%	Min. 95%	Min. 95%	Min. 95%
Dimensions	35 x 20 x 94,5 cm	35 x 20 x 94,5 cm	35 x 20 x 94,5 cm	35 x 20 x 94,5 cm
Weight	35 kg	37 kg	42 kg	45 kg

NITRO@SERVICE LINE



MADE IN ITALY

NITROGEN GENERATORS WITH PERMEABLE MEMBRANE SYSTEM FOR INFLATING TYRES OF CARS, VANS AND BUSES

- Minimum purity: 95%
- Built-in, oil separating and active carbon filters
- A: Filter blockage check instrument
- Automatic condensation overflow
- Air-nitrogen switch
- Nitrogen outlet pressure gauge
- Extra outlet for external tank
- 90 lt tank included (by Nitro@service 1200 / 3600)
- With trolley: 2 fixed wheels and 2 rotating wheels
- B: Inflating/deflating Michelin gun with Venturi meter and 8 mt spiral hose
- C: 20 caps for tyres inflated with nitrogen

OPTIONAL ACCESSORIES

Cod. 03.000.14

Kit of caps for tyres inflated with nitrogen, 100 pcs

Cod. 03.006.01

Kit of spare cartridges for Nitroservice 12000/24000, 3 pcs

Cod. 03.006.02

Kit of spare cartridges for Nitroservice 1200 / 3600, 2 pcs

Important: please specify the serial number in the order

STANDARD ACCESSORIES



NITRO@SERVICE Line	NITRO@SERVICE 1200 Cod. 03.002.40	NITRO@SERVICE 3600 Cod. 03.002.41	NITRO@SERVICE 12000 Cod. 03.002.42	NITRO@SERVICE 24000 Cod. 03.002.43
Flow capacity	1,2 Nm ³ /h 10 bar (145 PSI)	3,6 Nm ³ /h 10 bar (145 PSI)	12 Nm ³ /h 10 bar (181 PSI)	24 Nm ³ /h 10 bar (181 PSI)
Purity	Min. 95%	Min. 95%	Min. 95%	Min. 95%
Internal tank	90 lt (Nitro@service)	90 lt (Nitro@service)	Can work without external tank	Can work without external tank
Dimensions	60 x 44 x 132 cm	60 x 44 x 132 cm	60 x 44 x 132 cm	60 x 44 x 132 cm
Weight	75 kg	75 kg	65 kg	70 kg